



ENAC APPROVED

RPAS PPL 612



Rapid Field Charger

Quick charge capability, transportability, robustness and reliability are the features that mark Nimbus rapid field chargers.

General features

- Two outputs to manage the double battery set with dedicated displays and controls
- Multimode system (charge, discharge, cycle, store, balance)
- Charge functions suitable for all batteries of Nimbus RPAS, plus extra support for LiFe, Pb, NiMH and NiCd batteries
- Additional cell checker and low current charger
- Flame proof battery charge and storage well
- Embedded in a Peli Protector IP67 case
- Dustproof construction, designed to be tolerant to water splashes (sealed pots, internal protections, protected printed circuits)
- Effective cooling system designed to operate the unit with only a 5 cm opening of the Peli Protector case
- Compact solution thought to host a control station in the same Peli Protector case for safe transport
- 12 V cables with battery clips / BSK12 / cigar lighter connectors



Field charger: technical specifications

Total weight: 4500 g

Operating temperatures: - 10° C / + 40° C

Storage temperatures: -20° C / + 65° C

Dimensions: 339 x 295 x 152 mm

Strada Bertola Poligono, 19
10040 Lombardore (Torino), ITALIA
Tel+390119956481
Fax+390119958892
P.IVA 09434470010 - Cap. soc. i.v.: € 312.500,00
REA: TO-1051621

www.nimbus.aero

The contents shown in the text are for only information.
Nimbus Srl reserves to modify such contents at any time without notice.